DMG ChemisdPharmazeutische Fabrik GmbH Abbreviated 58(k) Premarket Notification March 30, 1999 Ionosit Bond

MAY 17

510(k) Summary

Trade Name:

Ionosit Bond

Sponsor:

DMG Chemisch-Pharmazeutische Fabrik GmbH

Elbgaustrasse 248

22547 Hamburg, Germany Registration No. 8010567

Device Gereric

Name:

Dental cement

Classification:

According to Section 513 of the Federal Food, Drug, and

Cosmetic Act, the device classification is Class II.

Predicate Device:

The proposed DMG Ionosit Bond material is substantially equivalent to the Vitrebond material marketed by 3M Dental Products, which was cleared for marketing by FDA in K962065 and K882821.

Product Description:

Ionosit Board is a light-cure, glass ionomer liner/base material which is supplied in the form of a powder and liquid that are mixed prior to use. The liquid component contains a light sensitive polymerizable acid; the powder contains a fluoride-releasing special reactive glass.

Indications for Use:

Ionosit Bond is indicated for use in lining and basing applications under composite, amalgam, ceramic and metal restorations.

Safety and Performance:

Substantial equivalence for this device was based solely on design and technical specifications; no performance or safety data was included in this premarket notification. The materials, performance specifications and essential design characteristics of the Ionosit Bond material are equivalent to those of the predicate device. The proposed Ionosit Bond material complies with FDA's Guidance for Dental Cements as well as ISO 9917-Part 2 (dental water-based cements).

Conclusion:

Based on the indications for use, technological characteristics, and comparison to the predicate device, the Ionosit Bond material has been shown to be safe and effective for its intended use

(5) Technological characteristic of the gloves.

a. Dimensions

Sizes	XS	S	M	L	XL
Length	240 mm	240 mm	240 mm	240 mm	240 mm
Width	80 < mm	80±10 mm	95±10 mm	111±10 mm	>111mm

Thickness

| 1. | Cuff (min) | 0.10 mm |
|----|------------------|---------|---------|---------|---------|---------|
| | | 0.10 mm |
| | Finger Tip (min) | 0.10 mm |

b. Physical Properties

1		Before aging		After aging at 70°C 168 hrs.	
Tensile Strength	:	21 Mpa		16 Mr	oa
Ultimate Elongation	:	700 % (r	min.)	600 %	(min.)

- (6) Performance data is the same as mentioned immediately above.
- (7) Clinical date is not needed for gloves or for most devices cleared by the 510 (K) process.
- (8) Non-clinical data We certify that these gloves meet ASTM D 3578 Standard. Meets FDA pinhole requirement. Meets labeling claim.